




Technical Data sonnenBatterie eco 9.43

	eco 9.43/5	eco 9.43/7.5	eco 9.43/10	eco 9.43/12.5	eco 9.43/15	
Nominal battery capacity in kWh	5.0	7.5	10.0	12.5	15.0	
Depth of discharge (DoD)	90%					
Cell technology	LFP (Lithium Iron Phosphate)					
Cabinet option 1 (5.0 kWh)						
Weight in kg	81	_	_	_	_	
Dimensions (H/W/D) in cm	88/67/23	-	-	-	-	
Cabinet option 2 (5.0 kWh-10.0	0 kWh)'					
Weight in kg	97	120	143	-	-	
Dimensions (H/W/D) in cm	137/67/23	137/67/23	137/67/23	-	-	
Cabinet option 3 (5.0 kWh-15.0	0 kWh)'					
Weight in kg	108	131	154	177	200	
Dimensions (H/W/D) in cm	186/67/23	186/67/23	186/67/23	186/67/23	186/67/23	
Nominal power (charging/discharging) in kW	2.5	3.3	3.3	3.3	3.3	
Max. inverter efficiency	95%					
Max. battery efficiency	98 %					
Ambient temperature range	-5°C - +45°C ²					
Dust and water protection	IP30					
Operating mode	single phase					





Technical Data sonnenBatterie eco 9.43

	eco 9.43/5	eco 9.43/7.5	eco 9.43/10	eco 9.43/12.5	eco 9.43/15		
Tests and directives	SGS T	SGS TÜV Saar, UN38.3, IEC 62133, DIN EN 62040-1, IEC 62619, AS/NZS 4777.2					
Battery service life		designed for 20 years					
Warranty		10 years³					
Cycles			10,000³				
Available options							

Multi-Touch-Display	7 inches			
sonnenWallmount	installation mount			

• 躇 enBatterie-Datasheet-eco-9.43-AU-180529

We reserve the right to make technical changes and updates without prior notice. Specific values, performance data and other information in this data sheet, brochures and other product information, as well as illustrations and drawings in these documents, are solely illustrative and are subject to ongoing revision and modification. We do not warrant the accuracy or completeness of any information in these documents unless otherwise explicitly stated. Only the information in order confirmation documents or purchase contracts is binding.

¹ There are two cabinet versions available. By default, the large cabinet is included (Dimensions H/W/D 98/67/23). If a small cabinet is needed for a storage battery of 5.0 kWh up to 10.0 kWh, this must be specified when ordering. ² Derating at approx. 35 °C. ³ Warranty on all parts. To learn more about our current warranty terms and conditions, please visit sonnenbatterie.de/en/terms-and-conditions or call our customer hotline and request a copy. Standard housing color: white. Housing color black only on request.